



THE UNIVERSITY
OF CHICAGO



The South Pole Telescope

...a status update

Kathryn K. Schaffer

Kavli Institute for Cosmological Physics, University of Chicago



The punchline:

We are entering the 2008 Winter Observing season with a sensitive new focal plane and an initial 100-deg² field. Lots learned from 2007, with analysis ongoing!

SPT Collaboration



William Holzapfel
Adrian Lee
Helmuth Spieler
Christian Reichardt
Bradford Benson
Martin Lueker
Jared Mehl
Tom Plagge
Dan Schwan
Erik Shirokoff



John Ruhl
Tom Montroy
Zak Staniszewski



Antony Stark



Joe Mohr



John Carlstrom (P.I)

Steve Padin (Proj. Manager)

Stephan Meyer

Clem Pryke

Tom Crawford

Jeff McMahon

Clarence Chang

Kathryn Schaffer

Joaquin Vieira

Ryan Keisler

Lindsey Bleem

Abigail Crites

Erik Leitch

Dana Hrubes, Keith Vanderlinde Winter 2008



Nils Halverson



Hsiao-Mei (Sherry) Cho



Matt Dobbs


Gil Holder



Lloyd Knox



Jason Dick

Science Goals of the SPT



1. Explore dark energy using a galaxy cluster survey: 4000 deg² survey to detect clusters through Sunyaev-Zeldovich (SZ) effect. With redshifts from optical followup, use dN/dz to constrain dark energy.
2. Fine angular scale CMB anisotropy
3. CMB Polarization (SPT-Pol)
~2010

Detecting Clusters through the SZ effect





Features:

- * Typical cluster sizes \sim few arcminutes.
- * Total SZ proportional to temperature-weighted mass.
- * SZ effect is independent of redshift.
- * Size of effect $< 1\text{mK}$


Challenges:

- * Uncertainty in mass-observable relation
- * Survey completeness/contamination: primary CMB anisotropy, radio galaxies, dusty galaxies, projection effects.




3 degrees at 90GHz
(Idealized! no noise,
no atmosphere...)


SPT Optical design




Schematic of the SPT, when Telescope is 'Docked' for access to the Receiver Cabin



- Simple optical design
- 10m primary - 1' beams at 150GHz.
- ~20 micron surface accuracy
- Multiple levels of shielding in design



Optics Cryostat




Optics Cryostat + Receiver




The SPT Receiver Array


180 mm; ~ 1 degree on sky



(Holzapfel and Lee, UC Berkeley)



Al/Ti TES



- 160 pixels on each wedge
- Transition Edge Sensor bolometers with $T_c \sim 500\text{mK}$
- 8 bolometers read out by a single SQUID using frequency-domain multiplexing

SPT 1st Year Deployment

Dec 14, 2006



Dec 16, 2006



Jan 3, 2007




- Jan 3, 2007 – Reflector/Primary Mirror mounted on Telescope
- Feb 12, 2007 - Receiver mounted on Telescope
- Feb 16, 2007 - First Light = Scans of Jupiter
- Feb 17, 2007 - Kicked out of South Pole


Feb 12, 2007




Feb 16, 2007



First Season Instrument: performance and challenges




FOCUS BEAMMAP 51



- NETs: $\sim 1500 \mu\text{K-CMB s}^{1/2}$
 - higher than optimal G and T_c
 - readout and G (thermal conductance) noise limited
 - high $1/f$ knee $\sim 2\text{-}3\text{Hz}$.
- Yield: max ~ 500 detectors, typical ~ 380 .
 - detector instabilities
 - cryogenic loading heated the squids
- Time-on-sky: cryogenic duty cycle was only $\sim 50\%$. Of the 50% of time that was used for observing, $\sim 1/3$ spent on calibration/pointing.
- Beam FWHMs: very close to expected
 - 95 GHz: $1.52 \pm 0.08'$ (predicted 1.51)
 - 150 GHz: $1.08 \pm 0.08'$ (predicted 1.01)
 - 220 GHz: $0.86 \pm 0.05'$ (predicted 0.78)

First season observing fields:

- 4000 sq. deg. SPT
- BCS 5h30 & 23h
- Boomerang (shallow & deep)
- ACBAR fields (approx.)



• Two sub regions of the Blanco Cosmology Survey (BCS)

Large field $\sim 35 \text{ deg}^2$ (BCS 5h30)

- 300 hours integration time
- Useful for cluster finding
- Sensitivity should be $\sim 40 \mu\text{K} / \text{arcmin beam}$

Small field $\sim 6 \text{ deg}^2$

- Located inside the large field
- 200 hours integration time
- small scale (high l cmb) to $\sim 20 \mu\text{K} / \text{arcmin beam}$

Analysis ongoing...
Biggest challenge: pointing models

SPT 2nd Year Upgrades


Nov. 2007: holography and adjustments




Nov./Dec. 2007: FTS



Feb. 2008
Final array installed




Dec./Jan. 2007: Receiver upgrades, telescope insulation



Feb. 14
Happy Valentines Day from SPT
(as1063 ~16 sigma detection
from 40-min observation, ~320 150GHz detectors)

Map made by Tom Crawford

Second Season Instrument: upgrades and initial performance




- Lower G detectors - better noise/sensitivity
- Detector design changes improved detector stability; also improved setup scripts for better yield, faster tuning
- Widened the bands for 150 and 220 GHz to ~ 45 GHz and ~ 50 GHz respectively (from ~ 30 and ~ 40 GHz)
- Major cryo upgrades - new PT415, better heat strapping, better wiring heat sinking... current cycles last >36 hours.

Band:	#Bolos:	NET ($\mu\text{Ks}^{1/2}$ -CMB)
90 GHz	~ 35	$\sim 1000+$
150 GHz	~ 350	~ 400
220 GHz	~ 200	~ 800

Preliminary
Estimates

Initial field for season two:

- 4000 sq. deg. SPT
- BCS 5h30 & 23h
- Boomerang (shallow & deep)
- ACBAR fields (approx.)



(also PISCO, SCS ...)

- A $\sim 100\text{deg}^2$ patch including the BCS 5h30 field
- Then, start hammering away at the final 4000-square-degree cluster survey region

Completing the cluster survey:

Stage I: Blanco Cosmology Survey (BCS)

- A 45 night program that began fall 2005 to survey 100 square deg (2.5 pct of SZ survey size) at Blanco 4m on Cerro Tololo
- <http://cosmology.uiuc.edu/BCS>


Stage II: Dark Energy Survey (DES)

- 5000 square deg G, R, I and Z bands
- 2005-2010: Construction of a new 3 square deg camera for the Blanco 4m
- 2010-2015: Survey Operations
- <https://www.darkenergysurvey.org/>

Warm-Fuzzy-Feeling Slide #1


Bullet cluster - 1es0657

2.25 hours observing time with ~300 150GHz detectors
minimally processed



Map made by Tom Plagge

Warm-Fuzzy-Feeling Slide #2



Preliminary,
handle with
care!

~60 hours of observing the
~100 square degree field.

Coadded 150GHz only, with
uncorrected pointing

RMS in map compared to L/R
difference map suggests
some of this structure is real...

Prospects pretty exciting for
this season's instrument!

Conclusions and Future Plans

- Successful first commissioning season - Telescope built, tested new technologies (PT, fMUX, large-format arrays) and learned a lot. Plus, science coming soon!
- 2008 instrument is sensitive enough to do some very interesting science

Upcoming:

- Install more 90GHz detectors next Austral Summer
- Continue cluster survey for 2+ more years (total)
- Install ground shield over the next two seasons
- Funded for 1000-element polarization sensitive instrument for early 2010



The South Pole Telescope Team

<http://spt.uchicago.edu>

