



EBEX
The E and B EXperiment

Michael Milligan
University of Minnesota



Collaboration

APC – Paris

Radek Stompor

Brown University

Andrei Korotkov
John Macaluso
Greg Tucker
Yuri Vinokurov

CalTech

Tomotake
Matsumura

Cardiff

Peter Ade
Enzo Pascale

Columbia University

Amber Miller
Britt Reichborn-
Kjennerud
Will Grainger

Harvard

Matias Zaldarriaga

IAS-Orsay

Nicolas Ponthieu

Imperial College

Andrew Jaffe

Lawrence Berkeley

National Lab

Julian Borrill

McGill University

Francois Aubin
Eric Bisonette
Matt Dobbs
Kevin MacDermid

Oxford

Brad Johnson

SISSA-Trieste

Carlo Baccigalupi
Sam Leach
Federico Stivoli

University of California/Berkeley

Adrian Lee
Xiaofan Meng
Huan Tran

University of California/San Diego

Tom Renbarger

University of Minnesota/Twin Cities

Asad Aboobaker
Shaul Hanany
Clay Hogen-Chin
Hannes Hubmayr
Terry Jones
Jeff Klein
Michael Milligan
Dan Polsgrove
Ilan Sagiv
Kyle Zilic

Weizmann Institute of Science

Lorne Levinson

**EBEX is funded by NASA
2004-2007 and 2007-2011**

- Detect or set upper bound on inflation B-mode


– Restrict T/S to $\sim \times 10$ better than now:

$T/S < 0.02$ at 2σ


(excluding systematic and foreground subtraction uncertainties)

EBEX 14 days


Planck 1 year




- Detect or set upper bound on B-mode
- Detect the lensing B-mode:
 - 5% error on amplitude of lensing power spectrum



- Detect or set upper bound on B-mode
- Detect the lensing B-mode
- Determine properties of polarized dust




Simulated CMB+Dust Reconstruction




- Simulate observed sky from dust + CMB + instrument noise (at three EBEX frequency bands)
- Systematic uncertainties not simulated
- Reconstruct dust + CMB maps (using parametric estimation)
- Less than $1/3\sigma$ penalty in CMB reconstruction for $l < 900$
- Unbiased recovery of CMB and dust power spectra


- Detect or set upper bound on B-mode
- Detect the lensing B-mode
- Determine properties of polarized dust
- Improve accuracy of cosmological parameters:
e.g. x2 improvement in limit on running of n




- concentrate on $20 < l < 1500$
- Detect B lensing signal:
~x5 stronger than dust
- Deal with only one foreground
- Use balloon to get firm handle on dust foreground
- Provide strong rejection of polarimetric systematics
- Use available technologies where practical



- Long duration balloon borne
- Use 1476 bolometric TES
- 3 Frequency bands: 150, 250, 410 GHz
- Resolution: 8' at all frequencies
- Polarimetry with half wave plate
- BLAST (+ BOOM, MAXIMA) balloon technologies




- Lensing B-mode: Reflecting Gregorian Dragone telescope
- Control of sidelobes: Cold aperture stop



- Polarimetry: Half Wave Plate + Grid
- Efficiency : Detection of two orthogonal states



- Modulation via continuous rotating HWP
- Sky signals appear at sidebands of $4f$
- Signal bandwidth defined by beam size and scan frequency



MAXIPOL:

- Q, U power spectra consistent with white noise to ~few mHz
- Level consistent with expected detector noise

AHWP Modulation Efficiency




EBEX:

- 5 stack achromatic HWP
- 0.98 efficiency for $120 < \nu < 420$ GHz
- Rotates at 5 Hz
- Sky signal in ~ 5 Hz sidebands of $4f = 24$ Hz

- HWP prototype bonded + thermally cycled
- ARC prototype bonded + thermally cycled
- AHWP now being bonded @ Cardiff
- Superconducting magnetic bearing tested end-to-end




Focal Plane



738 element array

139 element decagon

Single TES




Strehl > 0.85 at 250 GHz


- Total of 1476 detectors
- Maintained at 0.27 K
- 3 frequency bands/focal plane

- $G = 10 \text{ pWatt/K}$
- $NEP = 1.1e-17 \text{ W*rt(sec)}$ (150 GHz)
- $NEQ = 136 \text{ } \mu\text{K*rt(sec)}$ (150 GHz)
- $\tau = 3 \text{ msec}$,



- Total 350 sq. deg
- Constant elevation
- Speed: one Q,U per 1/3 beam
- Multiple visitations per pixel
- **Relatively uniform coverage**
- **Up to 10^8 samples/beam**



All (796) 150 GHz, 14 Day




Focal Plane/Readout Assembly




UMN

36 cm




UCB

UMN




NIST



UMN



McGill




LN2, LHe loads match design
LN2 hold time = 21 days (measured)
LHe hold time = 20 days (measured)




**Cable Suspension (a-la BLAST)
Pointing System (BLAST, MAXIMA, Boom)
Gondola integrated at Columbia U.
Pointing tests ongoing**



Science Scan Test



- 14 day flight
- 350 deg²
- ~20,000 8' pixels
- Low dust contrast (4 μ K rms)
- 796, 398, 282 TES detectors at 150, 250, 410 GHz
- 0.6 μ K/8' pixel - Q/U;
0.5 μ K/8' pixel - T
- North American flight: 2008




Extra Material






130 cm



Measured RMS Figure $< \lambda_{420}/14$

Optical Quality vs. Frequency




Over 6 Deg FOV


- 0.9 Strehl for 150 GHz
- 0.85 Strehl for 250, 420 GHz



Ground-based: relative polarization spectral response & polarization modulation efficiency




10 sub-bands per channel



Ground-based: antenna response (beam mapping), polarization rotation, coarse instrumental polarization


1.8 meter parabolic mirror on loan from BLAST

- surface quality
- beam size
- cost savings




EBEX gondola

Mapping beam:
scans source
just like in-flight
scan on sky




In-flight calibration: verifying ground-based measurements + absolute polarization spectral response


Comparison to WMAP temperature maps in EBEX scan area



Scans across Crab nebula




Scans across Jupiter




1. Absolute spectral response @ 150, 250 GHz
3. Polarization modulation efficiency
5. Beam map, absolute calibration @ 410 GHz
7. Instrumental polarization
9. Polarization rotation (a.k.a. cross-polarization)

Null correlation between E & B modes in EBEX data





Comparison to CMB dipole in EBEX scan area



Thermal Conductance:

- Removed metallization; Changed geometry
- $G_{\text{target}} = 30 \text{ pWatt/K}$
- $G_{\text{measured}} = 20, 23, 30, 80 \text{ pWatt/K}$






16 msec time constant (@50%)
limited by TES heat capacity =>
reduce heat capacity
(remove bling)

DFMUX noise < SQUID noise
SQUID Noise < Johnson noise



~x1.5 excess phonon noise
(@~50%) under investigation

- SQUID arrays (NIST)
- Digital Frequency Domain Multiplexing (McGill)



- LDB: 495 Watt for x12; 406 Watt for x16

- Measured 18.5 Watts/board
- Total of 495 Watt for LDB
- Flat heat pipes to conduct heat
- Constructed thermal model
- Tested heat sinking
- Baseplate at 17 C
- Results match simulations
- Warmest temperatures 43 C








Pathfinder for a Space Mission

- Detectors at low backgrounds
- Readout (low power DfMUX)
- Information about Foregrounds
- Information about Systematics

Polarization Rotation



- Half Wave Plate demonstrated successfully on MAXIPOL
- EBEX: 5-stack achromatic HWP; 0.98 efficiency for $120 < \nu < 450$ GHz



- Rotate at 6 Hz
- Signal at 24 Hz
- <10% attenuation from 3 msec time constant TES